

Basic Exercises

Job Submission to Grid Computing Environments

Pablo Orviz Fernández ¹

¹Instituto de Física de Cantabria - CSIC-UC
Grupo de Computación Distribuida y Grid

Grids & e-Science 2009
UIMP - Palacio de la Magdalena
Santander - Spain

Just for the first time..

User certificate and VO subscription

- 1 A certificate issued by a trusted Grid Certification Authority

Just for the first time..

User certificate and VO subscription

- 1 A certificate issued by a trusted Grid Certification Authority
 - Public & private keys copied in your User Interface's account

```
[tut01@i2gui01 ]$ ls -l .globus/  
-rw----- 1 tut01 tut 4495 Jun 8 12:44 usercert.pem  
-r----- 1 tut01 tut 963 Jun 8 12:44 userkey.pem
```

Just for the first time..

User certificate and VO subscription

- 1 A certificate issued by a trusted Grid Certification Authority
 - Public & private keys copied in your User Interface's account

```
[tut01@i2gui01 ]$ ls -l .globus/  
-rw----- 1 tut01 tut 4495 Jun 8 12:44 usercert.pem  
-r----- 1 tut01 tut 963 Jun 8 12:44 userkey.pem
```

- 2 Virtual Organization membership

Just for the first time..

User certificate and VO subscription

- 1 A certificate issued by a trusted Grid Certification Authority
 - Public & private keys copied in your User Interface's account

```
[tut01@i2gui01 ]$ ls -l .globus/  
-rw----- 1 tut01 tut 4495 Jun 8 12:44 usercert.pem  
-r----- 1 tut01 tut 963 Jun 8 12:44 userkey.pem
```

- 2 Virtual Organization membership
 - Managed by **VOMS servers**
 - Each one supports a set of VOs
 - User requests approved by a VO manager

Every time we want to access the Grid..

VOMS Proxy certificate

What is a VOMS Proxy certificate?

- Special kind of certificate that enables you to use Grid facilities during a certain period
- This certificate contains
 - Certificate credentials
 - VOMS extensions of your VO

Why do we need a proxy?

- In the Grid world it is often necessary for a remote service to act on a user's behalf

VOMS Proxy Certificate - Exercises

Create a VOMS proxy

- Log into your account in the User Interface

```
$ ssh tut01@i2gui01.ifca.es
```

VOMS Proxy Certificate - Exercises

Create a VOMS proxy

- Log into your account in the User Interface

```
$ ssh tut01@i2gui01.ifca.es
```

- Create the proxy certificate with VOMS extensions

```
[tut01@i2gui01 ~]$ voms-proxy-init -voms itut
```

- Passphrase: **temp1234**

VOMS Proxy Certificate - Exercises

Create a VOMS proxy

- Log into your account in the User Interface

```
$ ssh tut01@i2gui01.ifca.es
```

- Create the proxy certificate with VOMS extensions

```
[tut01@i2gui01 ~]$ voms-proxy-init -voms itut
```

- Passphrase: **temp1234**

```
Cannot find file or dir: /home/tut01/.glite/vomses  
Enter GRID pass phrase:  
Your identity: /C=PT/O=LIP/CN=user01  
Creating temporary proxy ..... Done  
Contacting i2g-voms.lip.pt:20003 [/C=PT/O=LIPCA/O=LIP/OU=Lisboa/CN=i2g-voms.lip.pt] "itut" Done  
Creating proxy ..... Done  
Your proxy is valid until Mon Jun 15 01:48:20 2009
```

VOMS Proxy Certificate - Exercises

Printing proxy certificate info

```
[tut01@i2gui01 ~]$ voms-proxy-info -all
```

VOMS Proxy Certificate - Exercises

Printing proxy certificate info

```
[tut01@i2gui01 ~]$ voms-proxy-info -all
```

```
subject          : /C=PT/O=LIP/CN=user01/CN=proxy
issuer           : /C=PT/O=LIP/CN=user01
identity         : /C=PT/O=LIP/CN=user01
type             : proxy
strength         : 1024 bits
path             : /tmp/x509up_u10402
timeleft         : 11:59:55
==== VO itut extension information ====
VO               : itut
subject          : /C=PT/O=LIP/CN=user01
issuer           : /C=PT/O=LIPCA/O=LIP/OU=Lisboa/CN=i2g-voms.lip.pt
attribute        : /itut/Role=NULL/Capability=NULL
timeleft         : 11:59:55
uri              : i2g-voms.lip.pt:20003
```

VOMS Proxy Certificate - Exercises

VOMS Proxy lifetime limit

Problem

Proxy lifetime limited to 12 hours by default

VOMS Proxy Certificate - Exercises

VOMS Proxy lifetime limit

Problem

Proxy lifetime limited to 12 hours by default

Solution 1

Extend it with `-valid H:M` option:

```
[tut01@i2gui01 ~]$ voms-proxy-init -voms itut -valid 120:00
```

VOMS Proxy Certificate - Exercises

VOMS Proxy lifetime limit

Problem

Proxy lifetime limited to 12 hours by default

Solution 1

Extend it with `-valid H:M` option:

```
[tut01@i2gui01 ~]$ voms-proxy-init -voms itut -valid 120:00
```

```
Cannot find file or dir: /home/tut01/.glite/vomses
Enter GRID pass phrase:
Your identity: /C=PT/O=LIP/CN=user01
Creating temporary proxy ..... Done
Contacting i2g-voms.lip.pt:20003 [/C=PT/O=LIPCA/O=LIP/OU=Lisboa/CN=i2g-voms.lip.pt] "itut" Done
Warning: i2g-voms.lip.pt:20003: The validity of this VOMS AC in your proxy is shortened to 86400 seconds!
Creating proxy ..... Done
```

VOMS Proxy Certificate - Exercises

VOMS Proxy lifetime limit

Problem

Proxy lifetime limited to 12 hours by default

VOMS Proxy Certificate - Exercises

VOMS Proxy lifetime limit

Problem

Proxy lifetime limited to 12 hours by default

Solution 2

Create a long-term proxy and store it in a **MyProxy Server**

VOMS Proxy Certificate - Exercises

VOMS Proxy lifetime limit

Problem

Proxy lifetime limited to 12 hours by default

Solution 2

Create a long-term proxy and store it in a **MyProxy Server**

```
[tut01@i2gui01 ~]$ myproxy-init -d -n -c 120
```

VOMS Proxy Certificate - Exercises

VOMS Proxy lifetime limit

Problem

Proxy lifetime limited to 12 hours by default

Solution 2

Create a long-term proxy and store it in a **MyProxy Server**

```
[tut01@i2gui01 ~]$ myproxy-init -d -n -c 120
```

```
Your identity: /C=PT/O=LIP/CN=user01  
Enter GRID pass phrase for this identity:  
Creating proxy ..... Done  
Proxy Verify OK  
Your proxy is valid until: Fri Jun 19 15:51:53 2009
```

A proxy valid for 120 hours (5.0 days) for user /C=PT/O=LIP/CN=user01 now exists on i2gpx01.ifca.es.

VOMS Proxy Certificate - Exercises

VOMS Proxy lifetime limit

Problem

Proxy lifetime limited to 12 hours by default

Solution 2

Create a long-term proxy and store it in a **MyProxy Server**

```
[tut01@i2gui01 ~]$ myproxy-init -d -n -c 120
```

```
Your identity: /C=PT/O=LIP/CN=user01  
Enter GRID pass phrase for this identity:  
Creating proxy ..... Done  
Proxy Verify OK  
Your proxy is valid until: Fri Jun 19 15:51:53 2009
```

A proxy valid for 120 hours (5.0 days) for user /C=PT/O=LIP/CN=user01 now exists on i2gpx01.ifca.es.

Long-term proxies need a VOMS proxy certificate (created with `voms-proxy-init`)

Information Service

Concepts

- Sites have to publish the information about their computing resources

Information Service

Concepts

- Sites have to publish the information about their computing resources
- This information follows a LDAP implementation

Information Service

Concepts

- Sites have to publish the information about their computing resources
- This information follows a LDAP implementation
- 2 main tools allow end users to easily request this info without querying directly the LDAP tree
 - **lcg-infosites**
 - **lcg-info**

Information Service - Exercises

lcg-infosites

- Used to obtain VO-specific information on existing Grid resources

```
[tut01@i2gui01 basic-js]$ lcg-infosites -vo itut ce
```

Information Service - Exercises

lcg-infosites

- Used to obtain VO-specific information on existing Grid resources

```
[tut01@i2gui01 basic-js]$ lcg-infosites -vo itut ce
```

#CPU	Free	Total Jobs	Running	Waiting	ComputingElement
24	24	0	0	0	i2ce.polgrid.pl:2119/jobmanager-pbs-itut
1004	57	0	0	0	i2gce01.ifca.es:2119/jobmanager-lcgpbs-infiniband
28	25	0	0	0	i2g-ce01.lip.pt:2119/jobmanager-lcgsge-itutgridsj
600	600	0	0	0	iwrce2.fzk.de:2119/jobmanager-lcgpbs-i2gpar
1004	57	0	0	0	i2gce01.ifca.es:2119/jobmanager-lcgpbs-infinibandlarge
8	8	0	0	0	ce.i2g.cyf-kr.edu.pl:2119/jobmanager-pbs-itut
1004	57	0	0	0	i2gce01.ifca.es:2119/jobmanager-lcgpbs-itut

Information Service - Exercises

lcg-infosites

- Used to obtain VO-specific information on existing Grid resources

```
[tut01@i2gui01 basic-js]$ lcg-infosites -vo itut ce
```

#CPU	Free	Total Jobs	Running	Waiting	ComputingElement
24	24	0	0	0	i2ce.polgrid.pl:2119/jobmanager-pbs-itut
1004	57	0	0	0	i2gce01.ifca.es:2119/jobmanager-lcgpbs-infiniband
28	25	0	0	0	i2g-ce01.lip.pt:2119/jobmanager-lcgsge-itutgridsj
600	600	0	0	0	iwrce2.fzk.de:2119/jobmanager-lcgpbs-i2gpar
1004	57	0	0	0	i2gce01.ifca.es:2119/jobmanager-lcgpbs-infinibandlarge
8	8	0	0	0	ce.i2g.cyf-kr.edu.pl:2119/jobmanager-pbs-itut
1004	57	0	0	0	i2gce01.ifca.es:2119/jobmanager-lcgpbs-itut

- 'ce' lists the Computing Elements that support itut VO

Information Service - Exercises

lcg-infosites

- Used to obtain VO-specific information on existing Grid resources

```
[tut01@i2gui01 basic-js]$ lcg-infosites -vo itut ce
```

#CPU	Free	Total Jobs	Running	Waiting	ComputingElement
24	24	0	0	0	i2ce.polgrid.pl:2119/jobmanager-pbs-itut
1004	57	0	0	0	i2gce01.ifca.es:2119/jobmanager-lcgpbs-infiniband
28	25	0	0	0	i2g-ce01.lip.pt:2119/jobmanager-lcgsge-itutgridsj
600	600	0	0	0	iwrce2.fzk.de:2119/jobmanager-lcgpbs-i2gpar
1004	57	0	0	0	i2gce01.ifca.es:2119/jobmanager-lcgpbs-infinibandlarge
8	8	0	0	0	ce.i2g.cyf-kr.edu.pl:2119/jobmanager-pbs-itut
1004	57	0	0	0	i2gce01.ifca.es:2119/jobmanager-lcgpbs-itut

- 'ce' lists the Computing Elements that support itut VO
- Other options: **se**, **closeSE**, **lfc**, **wms**, **fts**, **sitenames**, ..

Information Service - Exercises

lcg-info

- List either CEs or SEs satisfying a given set of conditions on their attributes

```
lcg-info [-list-ce — -list-se — -list-service — -list-site ] [-query <query>] [-attrs  
<attrs>]
```

Information Service - Exercises

lcg-info

- List either CEs or SEs satisfying a given set of conditions on their attributes

```
lcg-info [-list-ce — -list-se — -list-service — -list-site ] [-query <query>] [-attrs  
<attrs>]
```

- List of supported attributes

```
[tut01@i2gui01 basic-js]$ lcg-info -list-attrs
```

Information Service - Exercises

lcg-info

- List either CEs or SEs satisfying a given set of conditions on their attributes

```
lcg-info [-list-ce — -list-se — -list-service — -list-site ] [-query <query>] [-attrs <attrs>]
```

- List of supported attributes

```
[tut01@i2gui01 basic-js]$ lcg-info -list-attrs
```

Attribute name	Glue object class	Glue attribute name
EstRespTime	GlueCE	GlueCEStateEstimatedResponseTime
WorstRespTime	GlueCE	GlueCEStateWorstResponseTime
TotalJobs	GlueCE	GlueCEStateTotalJobs
TotalCPUs	GlueCE	GlueCEInfoTotalCPUs
[...]		

Information Service - Exercises

lcg-info - Simple Query

- List all the CEs that support itut V0

```
[tut01@i2gui01 basic-js]$ lcg-info -list-ce -vo itut
```

Information Service - Exercises

lcg-info - Simple Query

- List all the CEs that support itut VO

```
[tut01@i2gui01 basic-js]$ lcg-info --list-ce --vo itut
```

```
- CE: ce.i2g.cesga.es:2119/jobmanager-lcgsg-GRID_itut  
- CE: ce.i2g.cyf-kr.edu.pl:2119/jobmanager-pbs-itut  
- CE: i2ce.polgrid.pl:2119/jobmanager-pbs-itut  
- CE: i2g-ce01.lip.pt:2119/jobmanager-lcgsg-itutgridsj
```

```
[..]
```

Information Service - Exercises

lcg-info - Simple Query with constraints

- List all the CEs that support itut VO with 30-or-less running jobs

```
[tut01@i2gui01 basic-js]$ lcg-info -list-ce -vo itut  
-query 'VORunningJobs<=30'
```

Information Service - Exercises

lcg-info - Simple Query with constraints

- List all the CEs that support itut VO with 30-or-less running jobs

```
[tut01@i2gui01 basic-js]$ lcg-info --list-ce --vo itut  
--query 'VORunningJobs<=30'
```

- More comma-separated constraints can be added

```
[tut01@i2gui01 basic-js]$ lcg-info --list-ce --vo itut  
--query 'VORunningJobs<=30,OS=Scientific'
```

Information Service - Exercises

lcg-info - Simple Query with constraints and attribute listing

- List all the CEs that support itut VO with 30-or-less running jobs and therefore list useful information attributes

```
[tut01@i2gui01 basic-js]$ lcg-info -list-ce -vo itut  
-query 'VORunningJobs<=30'  
-attr 'CloseSE,FreeCPUs,TotalJobs,WaitingJobs,RunningJobs'
```

Information Service - Exercises

lcg-info - Simple Query with constraints and attribute listing

- List all the CEs that support itut VO with 30-or-less running jobs and therefore list useful information attributes

```
[tut01@i2gui01 basic-js]$ lcg-info --list-ce --vo itut  
--query 'VORunningJobs<=30'  
--attr 'CloseSE,FreeCPUs,TotalJobs,WaitingJobs,RunningJobs'
```

```
- CE:                i2g-ce01.lip.pt:2119/jobmanager-lcgsge-itutgridsj  
- CloseSE           se05.lip.pt  
                   i2g-se01.lip.pt  
- FreeCPUs          28  
- TotalJobs         0  
- WaitingJobs       0  
- RunningJobs       0  
  
- CE:                i2gce01.ifca.es:2119/jobmanager-lcgpbs-infiniband  
- CloseSE           i2gse01.ifca.es  
                   griddpm01.ifca.es  
- FreeCPUs          52  
- TotalJobs         0  
- WaitingJobs       0  
- RunningJobs       0  
[..]
```

JDL

Job Description Language

- **JDL** \implies language to describe job's requirements

JDL

Job Description Language

- **JDL** \implies language to describe job's requirements

JDL example - basic.jdl

```
Type = "Job";  
JobType = "Normal";  
RetryCount = "2"; Executable = /bin/sh";  
Arguments = "basic.sh";  
StdOutput = "basic.out";  
StdError = "basic.err";  
InputSandbox = "basic.sh";  
OutputSandbox = {"myscript.err","myscript.out"};
```

JDL

Job Description Language

- **JDL** \implies language to describe job's requirements

JDL example - basic.jdl

```
Type = "Job";  
JobType = "Normal";  
RetryCount = "2"; Executable = /bin/sh";  
Arguments = "basic.sh";  
StdOutput = "basic.out";  
StdError = "basic.err";  
InputSandbox = "basic.sh";  
OutputSandbox = {"myscript.err", "myscript.out"};
```

where

InputSandbox : files to be copied to the execution node

OutputSandbox : files to be copied back after job execution

JDL

Resource allocation

- JDL must be parsed to identify matching resources from the given sites

JDL

Resource allocation

- JDL must be parsed to identify matching resources from the given sites
- This is done by a service called **Resource Broker**. Therefore it also handles:

JDL

Resource allocation

- JDL must be parsed to identify matching resources from the given sites
- This is done by a service called **Resource Broker**. Therefore it also handles:
 - Final site selection (that matches your requirements)

JDL

Resource allocation

- JDL must be parsed to identify matching resources from the given sites
- This is done by a service called **Resource Broker**. Therefore it also handles:
 - Final site selection (that matches your requirements)
 - Storage of sandboxes

JDL

Resource allocation

- JDL must be parsed to identify matching resources from the given sites
- This is done by a service called **Resource Broker**. Therefore it also handles:
 - Final site selection (that matches your requirements)
 - Storage of sandboxes
 - Transitions within the status of jobs (scheduled, running, done, aborted..)

JDL

Resource allocation

- JDL must be parsed to identify matching resources from the given sites
- This is done by a service called **Resource Broker**. Therefore it also handles:
 - Final site selection (that matches your requirements)
 - Storage of sandboxes
 - Transitions within the status of jobs (scheduled, running, done, aborted..)
 - Proxy renewal (if you've used a MyProxy server)

JDL

Resource allocation

- JDL must be parsed to identify matching resources from the given sites
- This is done by a service called **Resource Broker**. Therefore it also handles:
 - Final site selection (that matches your requirements)
 - Storage of sandboxes
 - Transitions within the status of jobs (scheduled, running, done, aborted..)
 - Proxy renewal (if you've used a MyProxy server)
- Currently there are 2 main implementations:
 - Crossbroker (**i2g-job-*** commands)
 - gLite Workload Management System (**glite-wms-job-*** commands)

Job submission - Exercises

Check matching resources

- Go to `~/basic-js/` and take a look to `basic.jdl` and `basic.sh`

```
[tut01@i2gui01 basic-js]$ i2g-job-list-match basic.jdl
```

Job submission - Exercises

Check matching resources

- Go to `~/basic-js/` and take a look to `basic.jdl` and `basic.sh`

```
[tut01@i2gui01 basic-js]$ i2g-job-list-match basic.jdl
```

```
Selected Virtual Organisation name (from proxy certificate extension): itut  
Connecting to host i2grb01.ifca.es, port 7772
```

```
*****
```

COMPUTING ELEMENT IDs LIST

The following CE(s) matching your job requirements have been found:

CEId

```
iwrce2.fzk.de:2119/jobmanager-lcgpbs-i2gpar/itut  
i2gce01.ifca.es:2119/jobmanager-lcgpbs-itut/itut  
i2gce01.ifca.es:2119/jobmanager-lcgpbs-infinibandlarge/itut  
i2gce01.ifca.es:2119/jobmanager-lcgpbs-infiniband/itut  
i2g-ce01.lip.pt:2119/jobmanager-lcgsge-itutgridsdj/itut  
i2ce.polgrid.pl:2119/jobmanager-pbs-itut/itut  
ce.i2g.cyf-kr.edu.pl:2119/jobmanager-pbs-itut/itut  
ce.i2g.cesga.es:2119/jobmanager-lcgsge-GRID_itut/itut
```

```
*****
```

Job submission - Exercises

Submitting the job

```
[tut01@i2gui01 basic-js]$ i2g-job-submit basic.jdl
```

Job submission - Exercises

Submitting the job

```
[tut01@i2gui01 basic-js]$ i2g-job-submit basic.jdl
```

```
Selected Virtual Organisation name (from proxy certificate extension): itut  
Connecting to host i2grb01.ifca.es, port 7772  
Logging to host i2grb01.ifca.es, port 9002
```

```
*****
```

JOB SUBMIT OUTCOME

```
The job has been successfully submitted to the Network Server.  
Use i2g-job-status command to check job current status. Your job identifier is:
```

```
- https://i2grb01.ifca.es:9000/s8\_rgISqhoQ9JA0kkW3C0w
```

```
*****
```

Job submission - Exercises

Submitting the job

```
[tut01@i2gui01 basic-js]$ i2g-job-submit basic.jdl
```

```
Selected Virtual Organisation name (from proxy certificate extension): itut  
Connecting to host i2grb01.ifca.es, port 7772  
Logging to host i2grb01.ifca.es, port 9002
```

```
*****
```

JOB SUBMIT OUTCOME

```
The job has been successfully submitted to the Network Server.  
Use i2g-job-status command to check job current status. Your job identifier is:
```

```
- https://i2grb01.ifca.es:9000/s8\_rgISqhoQ9JA0kkW3C0w
```

```
*****
```

- -o option deviates the jobid to a file:

```
[tut01@i2gui01 basic-js]$ i2g-job-submit -o jobids basic.jdl
```

- This is useful when submitting a bunch of jobs

Job submission - Exercises

Checking the status of the job

```
[tut01@i2gui01 basic-js]$ i2g-job-status <job_id>
```

Job submission - Exercises

Checking the status of the job

```
[tut01@i2gui01 basic-js]$ i2g-job-status <job_id>
```

```
*****
```

BOOKKEEPING INFORMATION:

Status info for the Job : https://i2grb01.ifca.es:9000/s8_rglSqhoQ9JA0kkW3C0w

Current Status: Scheduled

Status Reason: Job successfully submitted to Globus

Destination: i2gce01.ifca.es:2119/jobmanager-lcgpbs-itut

reached on: Sun Jun 14 18:01:01 2009

```
*****
```

Job submission - Exercises

Checking the status of the job

```
[tut01@i2gui01 basic-js]$ i2g-job-status <job_id>
```

```
*****  
                                BOOKKEEPING INFORMATION:  
Status info for the Job : https://i2grb01.ifca.es:9000/s8_rglSqhoQ9JA0kkW3C0w  
Current Status: Scheduled  
Status Reason: Job successfully submitted to Globus  
Destination: i2gce01.ifca.es:2119/jobmanager-lcgpbs-itut  
reached on: Sun Jun 14 18:01:01 2009  
*****
```

- Job finishes as soon as Status parameter changes to Done
- If we've deviated the jobid to a file, we need -i option:

```
[tut01@i2gui01 basic-js]$ i2g-job-status -i <jobids_filename>
```

Job submission - Exercises

Retrieving the output

```
[tut01@i2gui01 basic-js]$ mkdir outputs
```



Job submission - Exercises

Retrieving the output

```
[tut01@i2gui01 basic-js]$ mkdir outputs
```

```
[tut01@i2gui01 basic-js]$ i2g-job-get-output -dir <output_dir>  
<job_id>
```

Job submission - Exercises

Retrieving the output

```
[tut01@i2gui01 basic-js]$ mkdir outputs
```

```
[tut01@i2gui01 basic-js]$ i2g-job-get-output -dir <output_dir>  
<job_id>
```

```
*****  
                                JOB GET OUTPUT OUTCOME  
Output sandbox files for the job:  
- https://i2grb01.ifca.es:9000//s8_rglSqhoQ9JA0kkW3C0w  
have been successfully retrieved and stored in the directory:  
/home/tut01/basic-js/outputs/tut01_s8_rglSqhoQ9JA0kkW3C0w  
*****
```

Job submission - Exercises

Retrieving the output

```
[tut01@i2gui01 basic-js]$ mkdir outputs
```

```
[tut01@i2gui01 basic-js]$ i2g-job-get-output -dir <output_dir>  
<job_id>
```

```
*****  
                                JOB GET OUTPUT OUTCOME  
Output sandbox files for the job:  
- https://i2grb01.ifca.es:9000//s8_rglSqhoQ9JA0kkW3C0w  
have been successfully retrieved and stored in the directory:  
/home/tut01/basic-js/outputs/tut01_s8_rglSqhoQ9JA0kkW3C0w  
*****
```

- Same as posted before for the `-i` option
- You can see the output sandbox in:

```
[tut01@i2gui01 basic-js]$ ls -l outputs/
```

Job submission - Exercises

Other i2g commands

There are several other commands like:

Job submission - Exercises

Other i2g commands

There are several other commands like:

```
[tut01@i2gui01 basic-js]$ i2g-job-get-logging-info <job_id>
```

Job submission - Exercises

Other i2g commands

There are several other commands like:

```
[tut01@i2gui01 basic-js]$ i2g-job-get-logging-info <job_id>
```

- Show the logging info of a submitted job
- Interesting for debugging cases

Job submission - Exercises

Other i2g commands

There are several other commands like:

```
[tut01@i2gui01 basic-js]$ i2g-job-get-logging-info <job_id>
```

- Show the logging info of a submitted job
- Interesting for debugging cases

```
[tut01@i2gui01 basic-js]$ i2g-job-cancel <job_id>
```

Job submission - Exercises

Other i2g commands

There are several other commands like:

```
[tut01@i2gui01 basic-js]$ i2g-job-get-logging-info <job_id>
```

- Show the logging info of a submitted job
- Interesting for debugging cases

```
[tut01@i2gui01 basic-js]$ i2g-job-cancel <job_id>
```

- Cancel and erases a submitted job
- No more info about the job after executing this command

Brief approach on gLite WMS commands



Brief approach on gLite WMS commands

- glite WMS uses the same concepts as Crossbroker does



Brief approach on gLite WMS commands

- glite WMS uses the same concepts as Crossbroker does
- The main difference is that glite WMS requires a delegated proxy before issuing any other command:

```
glite-wms-job-delegate-proxy -d <delegation_id>
```

Brief approach on gLite WMS commands

- glite WMS uses the same concepts as Crossbroker does
- The main difference is that glite WMS requires a delegated proxy before issuing any other command:

```
glite-wms-job-delegate-proxy -d <delegation_id>
```

- Equivalences

i2g-job-list-match	glite-wms-job-list-match
i2g-job-submit	glite-wms-job-submit
i2g-job-status	glite-wms-job-status
i2g-job-get-output	glite-wms-job-output
i2g-job-get-logging-info	glite-wms-job-info
i2g-job-cancel	glite-wms-job-cancel